



GREEN ANTIFREEZE 50/50

STARFIRE Green 50/50 is a premium ethylene glycol-based antifreeze that provides all season protection and when used as directed, offers superior 5-way protection against:

- Freeze-up/Boil Over
- Wet Sleeve Liner Pitting
- Scale Build Up
- Rust Corrosion
- Sludge/Clogging

APPLICATIONS

- Meets Light Duty ASTM D-3306 and Heavy Duty ASTM D-6210
- One universal product for Light Duty and Heavy Duty applications
- No need to add SCA's or chemical filters
- Compatible with all Conventional Green Antifreeze
- Blended with pure De-Ionized water for your quality needs.
- Phosphate free and meets low silicate standards
- May be used in virtually any engine cooling system

SPECIFICATIONS

- ASTM D-3306
- Ford ESE M97B44D
- Chrysler MS 7170
- GM 1825M
- GM 1899M
- ASTM D-6210
- Caterpillar
- GMC Truck
- John Deere
- Case
- Mack
- Detroit Diesel
- GE Locomotive
- Military CID A-A52624-A
- Orion/MCI Coaches
- Freightliner
- International
- TMC RP329

DESCRIPTION	TYPICAL VALUES	TEST METHOD
Appearance	Visual	Green
Specific Gravity at 60/60°F	1.053 – 1.083	D-1122
Freeze Point, at 50% max	-34°F	D-3321
pH at 50% Solution	8.5 – 10.	D-1287
Reserve Alkalinity min.	2.5	D-1121
Foam Test	150ml/5 sec	D-1881

BOIL OVER PROTECTION			
Type of Coolant Test	Atmospheric Pressure	14 LB. cap	15 LB. cap
Coolant Boiling	224°F	262°F	265°F
Coolant Freezing	-34°F	-34°F	-34°F