



## Full Synthetic CVT Fluid

**STARFIRE CHAIN & BELT FULL SYNTHETIC CVT FLUID** is specially formulated with a unique combination of full synthetic base stocks and an advanced additive technology designed for the specific demands of CVTs. This premium-quality product is recommended for use in most belt-driven Continuously Variable Transmissions, and it is not a replacement for ATF.

### APPLICATIONS

- Audi/VW (TL 52180; G 052 180; G 052 516)
- BMW 8322 0 136 376/8322 0 429 154 (EZL 799/EZL 799A)
- Daihatsu Amix CVTF-DC, Daihatsu AMIX CVTF-DFE
- Dodge/Jeep (NS-2/CVTF+4/Mopar CVT 4)
- Ford CFT30/WSS-M2C933-A/Motorcraft XT-7-QCFT
- GM/Saturn (DEX-CVT, CVTF I-Green 2)
- Honda (HMMF, HCF-2)
- Hyundai/Kia CVTF (SP-CVT 1)
- Mazda CVTF 3320
- Mercedes-Benz (236.20)
- Mercedes-Benz CVT28/MB-Approval 236.20
- Mini Cooper (EZL 799/EZL 799A/ZF CVT V1)
- Mitsubishi (CVTF-J1)
- Mitsubishi DiaQueen (CVTF-J1, CVTF-J4)
- Nissan (NS-1, NS-2, NS-3)
- Punch EZL 799/EZL 799A
- Renault ELFMATIC
- Shell Green 1V
- Subaru (NS-2/Lineartronic CVTF, i-CVTF, K0425Y0710) e-CVTF
- Suzuki (TC/NS-2/CVTF Green 1, CVTF Green 2, CVTF 3320)
- Toyota (TC, FE)

### Typical Properties

Viscosity: cSt @ 40°C	33.8
cSt@100°C	7.21
Viscosity Index	185
Pour Point, °F	-60
Specific Gravity @ 60°F (15.6°C)	0.8538
Gravity, °API	34.23
Color	Amber