



Full Synthetic Multi-Vehicle ATF

STARFIRE Full Synthetic Multi-Vehicle ATF is a high-performance, low viscosity multi-vehicle transmission fluid that is specially formulated for use in most planetary-gear transmissions applications. It is approved for use in General Motors automatic transmissions calling for DEXRON®-VI and Ford transmissions calling for MERCON® LV.

BENEFITS

- Full synthetic
- GM approved
- Protection against wear and transmission shudder
- Resistance to thickening due to high temperatures
- Friction stability to maintain smooth, consistent shift performance

Allison C-3
Allison C-4
Allison TES-389
Audi 5 HP LT71141, G 052162-A1/A2, G052 025 A2
Audi G 052 025, 052 162, 055 025
BMW 7045E, LA2634, LT71141
BMW JWS 3309, LA2634, ZF 5HP18FL, 5HP24, 5HP30, Mini
BMW P/N 83 22 0 0246 922, ETL-7045E
BMW P/N 83 22 0 024 359, ETL-8072B
BMW P/N 83 22 0 403 249, ETL-8072B
BMW P/N 83 22 9 407 765, LA 2634
BMW P/N 83 22 9 407 807, LT 711 41
CAT T0-2
Chrysler 8 and 9 speed transmissions
Chrysler AS68RC, Diamond SP-III
Chrysler P/N 05127382AA, P/N 68043742AA (DEX VI)
Daewoo LT 71141
Daihatsu AMMIX ATF D-II, D-III SP
DEXRON®-III G/H, DEXRON®-II, DEXRON®, AW1
Esso 71141
Fiat T-VI, JWS 3309
Ford FNR5
Ford M2C138-CJ
Ford M2C166H, 138CJ, 922A1, 924A, JWS 3309
Fuchs 3353
FUSO ATF-II, SPIII, A4

GMN10060
Hino Blue Ribbon ATF
Honda DW-1, Z-1
Hyundai/Kia/Mitsubishi Diamond SP-II and SP-III, RED-1, SP-IV
Hyundai/Kia SP-IV M, RR Dex-II/SP-II, JWS 3314, 9683
Hyundai NSWS9638
Idemitsu APOROIL ATF HP
Isuzu BESCO ATF-II, III
Isuzu 08200-9001 / Genuine ATF
Jaguar ATF 3403 M115, LT71141, ZF 5HP24, JLM20238
Jaguar P/N WSS-M2C922-A-1
Jaso M315-2013 1A, 1A-LV, 2A
JWS 3309, Any 3309
JWS 3324
Lexus JWS 3309
M315-2004 JASO 1A, 2A
MAG-1
MAN 339 Type V2
MAN 339 Type Z1, Z2, V1
Mazda ATF D-II, M-III, M-V, FZ, F-1, S-1, N-1, 3317
Mazda ATF M-III, MV, T-IV
MB 223.2, 236.1, 236.2, 236.10, 236.12, 236.41, 236.5, 236.6, 236.7, 236.8, 236.9
MERCON®, Ford ESP-M2C166-H
MERCON®LV (XT-10-QLV)
Mini Cooper T-IV
MINI P/N 83 22 0 402 413
Mitsubishi MA-1
Mitsubishi DiaQueen SK, AW, J2, J3, PA

Mopar AS 68 RC, JWS 3309
Mopar NAG-1
Nissan Matic-D, J, K
Nissan Matic, J, S
Opel
Peugeot ZF 4HP20
Porsche P/N 999 917 547 00 (A2)
Porsche ZF 5HP19FL, ZF 5HP20, LT71141, ATF 3403-M115, T-VI, JWS 3309
Saab P/N 22 717 466, 93 165 147 (AW-1)
Saturn P/N 21005966
Saturn T-IV, GM TASA, T-IV ATF, GM WS ATF
Scion
Shell 3403, LA2634, Texaco 7045-E, ETL-8072B
Shell 3403 M115
Subaru ATF 5AT, Dex II, AT OIL 5D06
Subaru ATF, ATF-HP
Suzuki ATF 2326, 2384K, JWS 3309, 3314
Texaco N402
Toyota D-II, D-III
Toyota T-II, T-III, T-IV, WS, Ford XT8QAW
Type A
Voith 55.6335 (G607)
Volvo Passenger Car (4 / 6 sp), Volvo 97340, 97341, 97342
Volvo P/N 1161540-8
VW 5 HP ZF5 HP 30, 18FL, 30, 19FL, 24A, G-055-025 A2, TL 521 62
VW G 052 025, 162, 099, 055 025

VW P/N GUS 000 162
VW TL52162 (LT71141)
ZF 845RE/870RE, ZF 8HP45/8HP70 /*8HP90
ZF all 3 & 4 speed trans.
ZF TE-ML 02F, TE-ML 03D, TE-ML 04D, TE-ML 09, TE-ML 11A
ZF TE-ML 14A, TE-ML 14B, TE-ML 14C, TE-ML 16L, ZF TE-ML 17C



TYPICAL PROPERTIES

VISCOSITY: cSt @ 40°C cSt @ 100°C	28.56 5.797
BROOKFIELD VISCOSITY AT -40°C, cP	10,300
VISCOSITY INDEX	151
POUR POINT, °F	-60
SPECIFIC GRAVITY @ 60°F (15.6 °C)	0.8468
GRAVITY, °API	35.6
COLOR	Red