



MERCON® V ATF

STARFIRE MERCON® V ATF is specially formulated with a unique combination of conventional base stocks and advanced additive technology to meet performance requirements of Ford automatic transmissions calling for MERCON® V fluid. Not for use in transmissions requiring Ford Type F fluid or Continuous Variable Transmissions (CVTs).

Licensed by Ford Motor Co., Inc. – License # M5141201.

STARFIRE MERCON® V ATF is suitable for use where the following automatic transmission fluids are recommended: automobile and truck automatic transmissions, power-shift transmissions and other types of service requiring an approved Ford MERCON® V automatic transmission fluid, DEXRON®-III (G, H), II (E, F) specifications, Honda Z-1, Nissan Matic-J and Toyota T-IV.

CLAIMS INFORMATION

Allison C-4	M315-2004 JASO 1A, 2A
Allison TES-389	MAN 339 Type Z1, Z2, V1
Audi G 052 025, 052 162, 055 025	Mazda ATF M-III, MV, T-IV
BMW 7045E, LA2634, LT71141	MB236.1, 2, 5, 6, 7, 9, 10, 11
BMW P/N 83 22 0 024 359, ETL-8072B	MERCON®, Ford ESP-M2C166-H
BMW P/N 83 22 0 0246 922, ETL-7045E	MERCON® V (XT-5-QM, XT-5-DM)
BMW P/N 83 22 0 403 249, ETL-8072B	MINI P/N 83 22 0 402 413
BMW P/N 83 22 9 407 765, LA 2634	Nissan Matic-D, J, K
BMW P/N 83 22 9 407 807, LT 711 41	Porsche P/N 999 917 547 00 (A2)
Chrysler AS68RC, Diamond SP-III	Saab P/N 22 717 466, 93 165 147 (AW-1)
Chrysler P/N 05127382AA, P/N 68043742AA	Saturn P/N 21005966
DEXRON®-III G/H, DEXRON® II, DEXRON®, AW1	Saturn T-IV, GM TASA, T-IV ATF, GM WS ATF
Esso 71141	Shell 3403, LA2634, Texaco 7045-E, ETL-8072B
Ford P/N XT-2-DX (MERC), Ford P/N XT-2-SM (SYN MERC)	Shell 3403 M115
Fuchs 3353	Subaru ATF, ATF-HP
Honda DW-1, Z-1	Suzuki 3314, 3317
Hyundai/Kia/Mitsubishi Diamond SP-II and SP-III, RED-1, SP-IV	Texaco N402
Hyundai NSWS9638	Toyota T-II, T-III, T-IV, WS, Ford XT8QAW
Idemitsu APOROIL ATF HP	Voith 55.6335 (G607)
Idemitsu K17	Volvo Passenger Car (4 / 6 sp), Volvo 97340, 97341, 97342
Isuzu 08200-9001 / Genuine ATF	Volvo P/N 1161540-8
Jaguar P/N WSS-M2C922-A-1	VW G 052 025, 162, 099, 055 025
JWS 3309, Any 3309	VW P/N GUS 000 162
JWS 3324	ZF TE-ML 03D, 04D, 05L, 09, 11B, 14A, 16L, 17C
	ZF TE-ML 14B



TYPICAL PROPERTIES

VISCOSITY: cSt @ 40°C	35.43
cSt @ 100°C	7.56
BROOKFIELD VISCOSITY @ -40°C, cP	11,300
VISCOSITY INDEX	189
FLASH, COC, °F	390
POUR POINT, °F	-60
SPECIFIC GRAVITY @ 60°F	0.8619
API GRAVITY	33.02
COLOR	Red