



PureCool Extended Life Antifreeze/Coolant

STARFIRE PureCool EXTENDED LIFE ANTIFREEZE/COOLANT is a premium, virgin, ethylene glycol-based product that may be used in all GM vehicles that require DEX-COOL® coolant, as well as other cars and light duty trucks with aluminum radiators.

WHEN USED AS DIRECTED:

- Meets GM 6277M, ASTM D3306 and ASTM D4985
- May be added to conventional antifreeze/coolant
- Protects aluminum and ANY other engine metals
- Meets GM and Ford performance specifications
- DEX-COOL® is a registered trademark of GM Corporation
- Available in concentrate and 50/50 pre-diluted formulas

PURECOOL	TYPICALS	ASTM
ASH CONTENT (50% BY VOLUME SOLUTION)	1.5% BY WEIGHT	D1119
PH (50% BY VOLUME SOLUTION)	10.0 – 11.0	D1287
RESERVE ALKALINITY	2.4	D1121
SPECIFIC GRAVITY AT 20/20°c (50% BY VOLUME SOLUTION)	1.064	D1122
FREEZING POINT (50% BY VOLUME SOLUTION)	-34°F	D1177
BOILING POINT (50% BY VOLUME SOLUTION)	227°F	D1120
FLASH POINT (TAG OPEN CUP) (70% BY VOLUME SOLUTION)	NONE	
FOAM TEST	50 ML/2.0 SEC.	D1881
COLOR	ORANGE	