Full Synthetic Universal ATF LV

STARFIRE Full Synthetic Universal ATF LV is a high-performance, low viscosity multi-vehicle transmission fluid that is specially formulated for use in most planetary-gear transmissions applications. It is suitable for use in General Motors automatic transmissions calling for DEXRON®-VI. This product is not recommended for Ford Type F, Continuously Variable Transmissions (CVT) or Double Clutch Transmissions (DCT) which require specialized OEM fluids.

BENEFITS

- Full synthetic
- Protection against wear and transmission shudder
- Resistance to thickening due to high temperatures
- Friction stability to maintain smooth, consistent shift performance

Allison C-3
Allison C-4
Allison TES-389
Audi 5 HP LT71141, G 052162-A1/A2, G052 025 A2
Audi G 052 025, 052 162, 055 025
BMW 7045E, LA2634, LT71141
BMW JWS 3309, LA2634,
ZF 5HP18FL, 5HP24, 5HP30, Mini
BMW P/N 83 22 0 0246 922, ETL-7045E
BMW P/N 83 22 0 024 359, ETL-8072B
BMW P/N 83 22 0 403 249, ETL-8072B
BMW P/N 83 22 9 407 765, LA 2634
BMW P/N 83 22 9 407 807, LT 711 41
CAT TO-2
Chrysler 8 and 9 speed transmissions
Chrysler AS68RC, AS69RC (T-IV)
Chrysler ATF +3, ATF+4
Diamond SP-III
Chrysler P/N 05127382AA, P/N 68043742AA (DEX VI)
Daewoo LT71141
Daihatsu AMMIX ATF D-II, D-III SP
DEXRON®-VI, DEXRON®-III, DEXRON® HP, DEXRON® (ULV)
Esso 71141
Fiat T-VI, JWS 3309
Ford FNR5
Ford M2C138-CJ
Ford M2C166H, 138CJ, 922A1, 924A, JWS 3309
Fuchs 3353
FUSO ATF-II, SPIII, A4
GMN10060
Hino Blue Ribbon ATF
Honda DW-1, Z-1
Hyundai/Kia/Mitsubishi Diamond SP-II and SP-III, RED-1, SP-IV
Hyundai/Kia SP-IV M, RR Dex-II/SP-II, JWS 3314, 9683
Honda 2.0 & 3.1
Hyundai NSWS9638
Idemitsu APOROIL ATF HP
Isuzu BESCO ATF-II, III
Isuzu 08200-9001 / Genuine ATF
Jaguar ATF 3403 M115, LT71141, ZF 5HP24, JLM20238
Jaguar P/N WSS-M2C922-A-1
Jaso M315-2013 1A, 1A-LV, 2A JWS 3309, Any 3309
JWS 3324
Lexus JWS 3309
M315-2004 JASO 1A, 2A
MAG-1
MAN 339 Type V2
MAN 339 Type Z1, Z2, V1
Mazda ATF D-II, M-III, M-V, FZ, F-1, S-1, N-1, 3317
Mazda ATF M-III, MV, T-IV
MB 223.2, 236.1, 236.2, 236.10, 236.12, 236.41, 236.5, 236.6, 236.7, 236.8, 236.9
MERCON®, Ford ESP-M2C166-H
MERCON®LV (XT-10-QLV)
MERCON® (ULV)
Mini Cooper T-IV
MINI P/N 83 22 0 402 413
Mitsubishi MA-1
Mitsubishi DiaQueen SK, AW, J2, J3, PA
Mopar AS 68 RC, JWS 3309
Mopar NAG-1
Nissan Matic-D, J, K, P
Nissan Matic, J, S
Opel
Peugeot ZF 4HP20
Porsche P/N 999 917 547 00 (A2)
Porsche ZF 5HP19FL, ZF 5HP20, LT71141, ATF 3403-M115, T-VI, JWS 3309
Saab P/N 22 717 466, 93 165 147 (AW-1)
Saturn P/N 21005966
Saturn T-IV, GM TASA, T-IV ATF, GM WS ATF
Scion
Shell 3403, LA2634, Texaco 7045-E, ETL-8072B
Shell 3403 M115
Subaru ATF 5AT, Dex II, AT OIL 5D06 Subaru ATF, ATF-HP
Suzuki ATF 2326, 2384K, JWS 3309, 3314
Texaco N402
Toyota D-II, D-III
Toyota T-II, T-III, T-IV, WS, Ford XT8QAW
Type A
Voith 55.6335 (G607)
Volvo Passenger Car (4 / 6 sp),
Volvo 97340, 97341, 97342
Volvo P/N 1161540-8
VW 5 HP ZF5 HP 30, 18FL, 30, 19FL, 24A, G-055-025 A2, TL 521 62
VW G 052 025, 162, 099, 055 025
VW P/N GUS 000 162
VW TL52162 (LT71141)
ZF 845RE/870RE, ZF 8HP45/8HP70 /*8HP90
ZF all 3 & 4 speed trans.
ZF TE-ML 02F, TE-ML 03D, TE-ML 04D, TE-ML 09, TE-ML 11A ZF TE-ML 14A, TE-ML 14B, TE-ML 14C, TE-ML 16L, ZF TE-ML 17C

**Please note that legislation in California prohibits recommending Suitable For Use in certain applications where the viscometrics do not match those of the official OEM specification. This product is not for sale or use in the State of California.*

**Some performance levels are limited by viscosity grade and fluid is Suitable for use in vehicles that are out of warranty.*

TYPICAL PROPERTIES	
VISCOSITY: cSt @ 40°C cSt @ 100°C	29.4 5.97
BROOKFIELD VISCOSITY AT -40°C, cP	14,460
VISCOSITY INDEX	155
POUR POINT, °C	-50
SPECIFIC GRAVITY @ 60°F (15.6 °C)	0.855
GRAVITY, °API	34.0
COLOR	Red